

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Россия +7(495)268-04-70

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://bandelin.nt-rt.ru/> || bni@nt-rt.ru

SONOREX TECHNOLOGY FA 220 FILTRATION



The FA filter unit is used to filter out dirt particles from the cleaning solution and enables the service life of the ultrasonic bath to be extended from a volume of 13 litres. The cleaning system is suitable for filtering aqueous cleaning media up to a maximum liquid temperature of 70 °C.

The filter unit FA consists of two filter housings made of polypropylene (PP) and a magnetically coupled centrifugal pump, which are mounted together on a bracket made of stainless steel sheet. The pre-filter serves to protect the pump from coarse contamination. The fine filter is used for depth filtration.

Further equipment includes a pressure switch, a ball valve, a switch box with ON button, a main switch and 2 metres of connection cable with earthing contact plug.

- The pressure switch switches off the pump when the fine filter is clogged. The fine filter can then be replaced.
- The ball valve can be used to adjust the flow rate.
- The pump of the filter unit must be below the liquid level of the tub.

ORDER NUMBER	8614
OPERATING VOLTAGE [V]	230 V EU plug
CE MARKING	Machinery Directive 2006 / 42 / EC, EMC Directive 2014 / 30 / EU, RoHS Directive 2011 / 65 / EU
PACKING LENGTH [MM]	0
PACKING WIDTH [MM]	0
PACKING DEPTH [MM]	0